

TECHNICAL SHEET

Genset model : EXEQ 25-1

Main data :

Type:	silent	ATS :	Optional
Fuel Tank running hours:	12H	Socket:	Included
Prime Power (KW/KVA):	25/25	Frequency, (HZ) :	50HZ
Standby Power (KW/KVA):	27.5/27.5	Voltage (V):	240
Genset size(mm) (L×W×H):	1950*740*1120	Phase No. :	1
N.W.(kgs):	810	G.W.(kgs)	815
Packing	Plastic Films	Controller :	AGM6120
Noise Level (dB @ 7m)	80		
Plug outlets	32A *1P *4 +15A*1P*4		

Engine data :

Alternator data :

Model :	YN27BZJ30	Model :	BC184G
Governor type:	Mechanical	Capacity (kVA):	25
Speed (r/min):	1500	Power factor:	1
Engine Size(mm)	920x550x850	AVR Type	SX460
Prime power(KW):	30	Efficiency:	0.87
Standby power(KW):	33	Bearing number:	1
Cylinder No.&Config.:	4-cylinder in-line	Leads number:	2
Fuel tank Vol.(L):	50	Voltage(V):	240
Displacement (L):	2.67	Voltage accuracy:	≤1.5%
Compression ratio :	17.5	Frequency, HZ :	50HZ
Oil capacity(L) :	6.5	Insulation class :	H
Electrical system (V):	12	Protection rate:	IP23
Coolant capacity(L) :	5.5	Excitation system :	Brushless
Cooling:	Forced water-cooling	Connection type:	/
Aspiration :	Turbocharged	Short-circuit current :	1.1
Starting Method	Electric	Connection :	SAE 3# / 11,5"