

TECHNICAL SHEET

Genset model : EXEQ 25-3

Main data :

Type:	silent	ATS :	Optional
Fuel Tank running hours:	12H	Socket:	Included
Prime Power (KW/KVA):	20/25	Frequency, (HZ) :	50HZ
Standby Power (KW/KVA):	22/27.5	Voltage (V):	240V/415V
Genset size(mm) (L×W×H):	1850*740*1200	Phase No. :	3
N.W.(kgs):	685	G.W.(kgs)	695
Packing	Plastic Films	Controller :	AGM6120
Noise Level (dB @ 7m)	80		
Plug outlets	20A *3P *2 +15A*1P*2+32A *3P *2 +32A*1P*2		

Engine data :

Alternator data :

Model :	K4100DS	Model :	BC184F
Governor type:	Mechanical	Capacity (kVA):	25
Speed (r/min):	1500	Power factor:	0.8
Engine Size(mm)	770x520x680	AVR Type	SX460
Prime power(KW):	30.1	Efficiency:	0.817
Standby power(KW):	33.0	Bearing number:	1
Cylinder No.&Config.:	4-cylinder in-line	Leads number:	12
Fuel tank Vol.(L):	50	Voltage(V):	415
Displacement (L):	2.7	Voltage accuracy:	≤1.5%
Compression ratio :	18:1	Frequency, HZ :	50HZ
Oil capacity(L) :	7	Insulation class :	H
Electrical system (V):	12	Protection rate:	IP23
Coolant capacity(L) :	12	Excitation system :	Brushless
Cooling:	Forced water-cooling	Connection type:	Y-type connection
Aspiration :	Natural	Short-circuit current :	1.1
Starting Method	Electric	Connection :	SAE 3# / 11,5"