



Generator Specifications

Genset model : KB-13-3			
Main data :			
TYPE	Silent	Controller :	Deepsea 4620
Prime Power (KW/KVA):	9/11.3	ATS :	optional
Standby Power (KW/KVA):	10/12.5	Socket:	3P 20A*2, 1P15*2
Frequency, (HZ) :	50	Breaker	3P 20A*2, 1P16*2
Voltage (V):	415/240	N.W.(kgs):	610
Phase No. :	3	G.W.(kgs)	615
Fuel Tank running hours:	22	Genset size(mm) (L×W×H):	1950*850*1150
Packing	Plastic Films	Noise Standard	65dB @ 7m
Engine data :		Alternator data :	
Model :	V1505	Model :	SOL1-L1
Brand	KUBOTA	Brand	STAMFORD
Governor type:	Mechanical	Capacity (kVA):	12.5
Speed (r/min):	1500	Capacity (kw):	10
Engine Size(mm)	636.8×392.3×607.1	Phase	3
Bore x Stroke (mm)	78x78.4	Voltage(V):	415/240
Prime power(KW):	11.1	Frequency (HZ) :	50
Standby power(KW):	12.5	RPM	1500
Cylinder No.&Config.:	4	Current(A)	17.4
Fuel tank Vol.(L):	58	Power factor:	0.8
Fuel Cosumption.(g/kw.h):	247	AVR Type	AS540
Displacement (L):	1.498	Efficiency:	82.4
Compression ratio :	24	Bearing number:	1
Oil capacity(L) :	6.7	Leads number:	12
Electrical system (V-KW):	12	Voltage Regulation:	≤±1%
Coolant capacity (Radiator) (L) :	5.6	Insulation class :	H
Coolant capacity (Engine) (L) :	1.07	Protection rate:	IP23
Cooling:	Water cool	Excitation system :	Brushless
Aspiration :	Natural	Connection type:	Series star connect
Starting Method	Electric	Connection :	SAE 3# / 11,5"